



pyropanel

Fire Doors

Standard Fire Rated Hinged Doorsets

(1 and 2 hour rating or SABS class A,B & D)

(Specifications for all other pyropanel fire rated doorsets are available on request.)

1 Hour or 2 Hour Fire Rated Doorsets

Supply and install Pyropanel fire rated doorsets in strict accordance with the manufacturer's instructions and in compliance with SABS 1253:2016 for a 60 or 120 minute fire rating with 3.6mm treated commercial ply or masonite suitable for painting on both sides. Including intumescent strip to top of door, hardwood edges, specified ironmongery and hinged one side to suitable 1.6mm gauge red oxide primed mild steel / galvanized steel frame.

1. Single Leaf door 810 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
2. Unequal Leaf Double door 1200 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
3. Equal Leaf Double door 1620 x 2030 x 48mm including frame suitable for 115mm / 230mm brick wall.
4. Single Leaf door 810 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass and frame suitable for 115mm / 230mm brick wall.
5. Unequal Leaf Double door 1200 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass to each leaf and frame suitable for 115mm / 230mm brick wall.
6. Equal Leaf Double door 1620 x 2030 x 48mm including 100 x 300mm vision panel with Pyroceramic fire resistant glass to each leaf and frame suitable for 115mm / 230mm brick wall.
7. Frames suitable for fire rated drywalls are available on request.

All installations to be done in accordance with SABISA guidelines.

Specifications are available on Autospec and our website.

Fire Retardant with a classification according to SANS 1253:2016

Pyropanel fire doors in South Africa have the required test reports, are manufactured in accordance with SANS 1253:2016 and all doors are tagged accordingly. This gives assurance that all of the Pyropanel doors are manufactured to the highest standard and are certain to provide the protection and safety required.

General

All Pyropanel fire doorsets are available with Pyroceramic or Georgian wire view panels as per SANS requirements and steel kick plates to various heights were required. All doors are supplied with metal identification tags on the door leaf and frame displaying the doorset number, the date of manufacture, the class / fire rating of the door and the SANS permit number.

All doors are manufacture, labelled and supplied in strict accordance with SANS 1253:2016